

THE BOARD OF DIRECTORS OF THE KELSEYVILLE COUNTY WATERWORKS
DISTRICT NO. 3 , COUNTY OF LAKE, STATE OF CALIFORNIA

ORDINANCE NO. _____

AN ORDINANCE AMENDING ORD NO. 1462, SECTION 1 OF APPENDIX D- CROSS-
CONNECTION CONTROL PROGRAM, ESTABLISHING A CROSS-CONTROL PROGRAM
TO PROTECT THE PUBLIC WATER SYSTEMS, IS HEREBY REVISED TO MEET
CURRENT STANDARDS SET FORTH BY THE STATE OF CALIFORNIA CROSS-
CONNECTION CONTROL POLICY HANDBOOK.

THE BOARD OF DIRECTORS OF THE KELSEYVILLE COUNTY WATERWORKS
DISTRICT NO. 3 IN THE STATE OF CALIFORNIA ORDAINS AS FOLLOWS:

SECTION ONE: SECTION 1, APPENDIX D OF THE CROSS-CONNECTION CONTROL
PROGRAM IS HEREBY AMENDED TO READ AS FOLLOWS:

SECTION 1. PROTECTION OF PUBLIC WATER SYSTEMS

Section 1.1. Purpose and Intent.

Pursuant to the California Cross-Connection Control Policy Handbook in conjunction
with Assembly Bill 1671, passed on October 6, 2017, and section 116555.5 of the Health
and Safety Code a Cross-Connection Control Program is hereby established in
Kelseyville County Waterworks District No. 3 for the following purposes:

- (a) To protect the public water supply from the occurrence of backflow into the Public
Water System. To protect the public from contamination or pollution from any onsite
hazards by eliminating or isolating said hazards and by implementing the installation,
maintenance and testing of approved backflow prevention assembly devices. By
enforcing methods of protection such as an approved air gap to protect against the
threat posed by many conditions typically found on a user's premises.
- (b) To eliminate or isolate existing connections or potential connections between drinking
water systems and other sources of water that are not approved as safe and potable for
human consumption.
- (c) To eliminate or isolate actual or potential cross-connections between drinking water
systems and other sources of water, liquids or any other unapproved substances that
may jeopardize the safety of the drinking water supply.
- (d) To prevent the making of cross-connections in the future.

Section 1.2. Definitions.

For this Ordinance, the following terms shall have the following meanings.

- (a) "*Air-gap separation*" or "*AG*" means a physical vertical separation of at least two (2)
times the effective opening, as defined in section 207.0 of the California Plumbing
Code, between the free-flowing discharge end of a potable water supply pipeline and
the flood level of an open or non-pressurized receiving vessel, and in no case less
than one (1) inch.

- (b) “*Auxiliary water supply*” means a source of water, other than an approved water supply, that is either used or equipped or can be equipped to be used as a water supply and is located on the premises of, or available to, a water user.
- (c) “*Backflow*” means an undesired or unintended reversal of flow of water and/or other liquids, gases, or other substances into a public water system’s distribution system or approved water supply.
- (d) “*Backflow prevention assembly*” or “BPA” means a mechanical assembly designed and constructed to prevent backflow, such that while in-line it can be maintained and its ability to prevent backflow, as designed, can be field tested, inspected and evaluated.
- (e) “*Backflow prevention assembly tester*” means a person who is certified as a backflow prevention assembly tester.
- (f) “*Cross-connection*” means any actual or potential connection or structural arrangement between a public water system, including a piping system connected to the public water system located on the premises of a water user or available to the water user, and any source or distribution system containing liquid, gas, or other substances not from an approved water supply.
- (g) “*Cross-Connection Control Specialist*” or “*Program Coordinator*” means a person who is certified as a cross-connection control specialist.
- (h) “*District water system*” means a system of water delivery operated and maintained by the Kelseyville County Waterworks District No. 3 formed pursuant to Section 55000 et seq. of the Water Code of the State of California.
- (i) “*Hazard Assessment*” means an evaluation of a user premises designed to evaluate the types and degrees of hazard at a user’s premises.
- (j) “*High hazard cross-connection*” means a cross-connection that poses a threat to the potability or safety of the public water supply. Materials entering the public water supply through a high hazard cross-connection are contaminants or health hazards.
- (k) “*Low hazard cross-connection*” means a cross-connection that has been found to not pose a threat to the potability or safety of the public water supply but may adversely affect the aesthetic quality of the potable water supply. Materials entering the public water supply through a low hazard cross-connection are pollutants or non-health hazards.
- (l) “*Owner of the premises*” means the person who owns the property served, or is readily capable of being served, with water via a service connection with a public water system.
- (m) “*Premise*” or “*premises*” means land and everything appurtenant thereto, including but not limited to, buildings, structures, and mobile homes.
- (n) “*Service connection*” means either the point where a water user’s piping is connected to a water system or the point in a water system where the approved water supply can be protected from backflow using an air gap or backflow prevention assembly.

Section 1.3. Cross-Connection and Protection Requirements.

3.1. Except as otherwise provided by this Ordinance, no person or entity shall cause a connection to be made between plumbing pipes, plumbing fixtures or appurtenances thereof served with water supplied by Kelseyville County Waterworks District No. 3 and plumbing pipes, plumbing fixtures or appliances thereof served by any other source of water.

3.2. Except as otherwise provided by this Ordinance, no person or entity shall install or use plumbing pipes, plumbing fixtures of appurtenances thereof which by their construction or means of hook-up, may permit a backflow of water or any other substance into a Kelseyville Water/Wastewater District #3 or into the service system of a consumer of water from such a system.

Section 1.4. Permit Required for Cross-Connection.

4.1 Any person or entity that installs or maintains a cross-connection or potential cross-connection either direct or indirect on any premise for construction purposes shall obtain a permit for such cross-connection from Special Districts Administration.

4.2. As a condition for the issuance of such permit, the person or entity wishing to maintain a temporary cross-connection shall install an approved backflow prevention assembly of the appropriate protection deemed by the Program Coordinator commiserate with the degree of hazard set forth by the California Cross Connection Control Handbook.

4.3. Installation of an approved backflow prevention assembly shall be required under the following circumstances.

(a) An approved backflow prevention assembly shall be installed at each service connection of the Kelseyville County Waterworks District No. #3 system where the premises served are also served by an auxiliary water supply not approved by the public health agency having jurisdiction.

(b) An approved backflow prevention assembly shall be installed at each service connection of the Kelseyville County Waterworks District No. #3 where the premises served has upon it any liquid or substance that potentially may enter the district water system. Such liquid or substance includes, but is not limited to, waters originating from a district water system which have been contaminated below the health standards established for a district water system.

Section 1.5. Requirements for Installation of Backflow Prevention Assemblies.

5.1 When a backflow prevention assembly is required to be installed pursuant to this Ordinance, the following shall apply.

(a) Any person or entity that is required to install a backflow prevention assembly pursuant to this Ordinance shall first obtain a permit for such installation from Special Districts Administration.

(b) Any backflow prevention assembly installed must be approved for potable water by the Foundation for Cross-Connection Control and Hydraulic Research of the University of Southern California unless otherwise stated in this Ordinance.

(c) Backflow prevention assemblies shall be installed in accordance with the Kelseyville Water Design and Construction Standards, along with methods of installation prescribed in the University of Southern California Cross-Connection Control Manual unless otherwise stated in writing by the Program Coordinator with Special Districts Administrator approval.

(d) Any person or entity which owns any premises where a backflow prevention assembly has been installed shall have such device inspected annually by an American Water Works Association Certified Backflow Tester pursuant to the California Cross Connection Control Policy Handbook. Backflow test reports will be submitted to Special Districts Administration no later than the annual test date to avoid service interruption.

(e) The Kelseyville County Waterworks District No. 3 shall not be liable for any costs for the inspection, repair, or maintenance of any such backflow prevention

assemblies installed pursuant to this Ordinance. All such costs shall be borne by the owner of the premises.

Section 1.6. Installations of Backflow Prevention Assemblies for Premises with Existing Cross-Connections.

6.1 Upon adoption of this Ordinance, the Cross Connection Control Specialist shall conduct hazard assessment surveys of all premises affected by the requirements of this Ordinance to determine those premises which have actual cross-connections, potential cross-connections, or hazards that may pose a threat to the water system.

6.2 The owner of each premises affected by the requirements of this Ordinance as determined by the Cross Connection Control Specialist with approval of the Special Districts Administrator, shall install or cause to be installed an approved backflow prevention assembly within ninety (90) days of receiving notice.

6.3 Upon the determination by the Cross Connection Control Specialist that a backflow prevention assembly is required upon the premises, the Cross Control Specialist shall serve notice upon the owner of said premise with approval from the Special Districts Administrator as determined from the last assessment roll, by depositing in the mail, postage prepaid, certified, return receipt requested and a notice that the steps in which the owner of the premises must take to comply with such provisions.

6.4 Within ninety (90) days of receiving the notice required by subsection 6.3 above, the owner of the premises shall obtain a permit pursuant to the provisions of this Ordinance and install the required backflow prevention assembly following the procedures set forth in subject 5.1 subdivision (c) of this Ordinance. The total cost of such installation shall be borne by the owner of the premises.

Section 1.7. Discontinuance of Service.

7.1 Service of water to any premises served by a district water system may be discontinued for noncompliance with the provisions of this Ordinance. Service shall be restored only upon compliance with the provisions of this Ordinance.

Section 1.8. Right of Entry.

8.1 Cross Connection Control Specialist or their designee shall inspect premises for noncompliance with the provisions of this Ordinance. They shall carry the proper credentials of this office. Upon exhibition of their credentials they shall have the right of entry during usual business hours for the performance of their duties, including conducting hazard assessments. This right of entry shall be a condition of water service in order to provide assurance that the continuation of service to the premises will not be detrimental to the health, safety and welfare of the people throughout the district water system.

Section 1.9 Certification of Applicant as Tester.

9.1 Each applicant shall be a certified backflow tester and shall provide proper credentials to Special Districts Administration in order to test within the district water system. Applicants shall hold a valid backflow tester certification from the American Water Works Association or approved equivalent by the State of California.

9.2 Each American Water Works Association certified backflow tester applicant shall furnish evidence to show that he has available the necessary tools and equipment to properly test such devices. Tester equipment calibration must be submitted to Special Districts Admin office annually and tester certification must be submitted every three years to the Special Districts Administration office to be eligible to test within the

district. The applicant shall be responsible for the competency and accuracy of all tests and reports prepared and submitted to Special Districts Administration.

9.3 The applicant's certification may be revoked or suspended from testing within the district water system for unsatisfactory testing, unsatisfactory repairs, or filing a report that misrepresents the condition of the backflow prevention assembly tested.

SECTION TWO: SECTION 2, APPENDIX D OF THE CROSS-CONNECTION CONTROL PROGRAM IS HEREBY AMENDED TO READ AS FOLLOWS:

SECTION 2. SCOPE

This Ordinance shall apply to the Kelseyville County Waterworks District No. 3 service area.

SECTION THREE: ENVIRONMENTAL REVIEW

The Board of Directors of the Kelseyville County Waterworks District No. 3 hereby finds that it can be seen with certainty that there is no possibility that the adoption of this Ordinance will have a significant effect on the environment because the Ordinance consists only of administrative changes by clarifying existing procedures and requirements, and it does not authorize or result in any physical changes to the environment or any increases in development intensity. It is therefore exempt from any California Environmental Quality Act (CEQA) review pursuant to Section 15061(b)(3) of Title 14 of the California Code of Regulations.

SECTION FOUR: All ordinances or parts of ordinances or resolutions or parts of resolutions in conflict herewith are hereby repealed to the extent of such conflict and no further.

SECTION FIVE: This Ordinance shall take effect on the _____ day of _____, 2026, and before the expiration of fifteen (15) days after its passage, it shall be published at least once in a newspaper of general circulation printed and published in the County of Lake.

The foregoing Ordinance was introduced before the Board of Directors of the Kelseyville County Waterworks District No. 3 on the _____ day of _____, 2026 and passed by the following vote:

AYES:

NOES:

ABSENT OR NOT VOTING:

Chair, Board of Directors

ATTEST: SUSAN PARKER
 Clerk of the Board

By: _____

1 APPROVED AS TO FORM: LLOYD GUINTIVANO
2 County Counsel

3 By: _____

4 Joseph Wankmueller
5 Deputy County Counsel
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28